Xmotor GB系列无刷云台电机
Xmotor Brushless Gimbal Outrunner

Item NO.	Name/Description	Weight(g)	Motor dimension[D x L] (mm)	Stator dimension[d x l] (mm)	Configuration	Copper wire(OD, mm)	Turns	Winding type	Max nominal voltage(V)	Resistance(Ri)(Ohm)	Idle current@10V(mA)	Max. stall current(A)	Diameter of Shaft(mm)	Length of shaft (mm)	Stator mounting holes [Pitch, Size](mm)	Rotor mounting holes [Pitch, Size] (mm)	Flexible wire solder board	Max. weight of gimbal/camera(kg)	Memo
51132	XM2826GB	41	27.8x25.4	22x08	12N14P	0.17	83	WYE	16	12.6Ω	97	1.0	4.0	12	16, 4xM2.5	10, 4xM2.5	Y	**0.4**	Long shaft w/ adapter
51133	XM2826GB-SS	38	27.8x25.4	22x08	12N14P	0.17	83	WYE	16	12.6Ω	97	1.0	4.0	N/A	16, 4xM2.5	10, 4xM2.5	Y	**0.4**	Shorten shaft
51134	XM3530GB	63	35x26.5	28x08	12N14P	0.21	87	WYE	25	9.0Ω	106	1.4	4.0	12	19, 4xM3	12, 4xM3	Y	**0.8**	Long shaft w/ adapter
51135	XM3530GB-SS	60	35x26.5	28x08	12N14P	0.21	87	WYE	25	9.0Ω	106	1.4	4.0	N/A	19, 4xM3	12, 4xM3	Y	**0.8**	Shorten shaft
51136	XM4010GB	79	39.5x27.7	34.5x10	24N28P	0.17	72	WYE	25	27.3Ω	87	1.1	4.0	12	19, 4xM3	12, 4xM3	Y	**1.3**	Long shaft w/ adapter
51137	XM4010GB-SS	75	39.5x27.7	34.5x10	24N28P	0.17	72	WYE	25	27.3Ω	87	1.1	4.0	N/A	19, 4xM3	12, 4xM3	Y	**1.3**	Shorten shaft
51138	XM5010GB	123	49x30.8	43.4x10	24N28P	0.25	55	WYE	25	9.3Ω	104	1.8	6.0	16	25, 4xM3	12, 4xM3	Y	**1.6**	For pitch & roll axis of DSLR camera
51139	XM5010GB-SS	117	49x30.8	43.4x10	24N28P	0.25	55	WYE	25	9.3Ω	104	1.8	6.0	N/A	25, 4xM3	12, 4xM3	Y	**1.6**	
51140	XM5015GB	163	49x35.8	43.4x15	24N28P	0.25	55	WYE	25	12.3Ω	94	2.1	6.0	16	25, 4xM3	12, 4xM3	Y	**2.4**	For yaw axis of DSLR camera & Frame
51141	XM5015GB-SS	154	49x35.8	43.4x15	24N28P	0.25	55	WYE	25	12.3Ω	94	2.1	6.0	N/A	25, 4xM3	12, 4xM3	Y	**2.4**	
51142	XM7010GB	261	69x35.5	61.5x10	24N28P	0.30	90	WYE	25	11.5Ω	92	2.5	8.0	20	30, 4xM4	15, 4xM3	Y	**3.3**	For pitch & roll axis of RED EPIC(3kg)
51143	XM7010GB-SS	246	69x35.5	61.5x10	24N28P	0.30	90	WYE	25	11.5Ω	92	2.5	8.0	N/A	30, 4xM4	15, 4xM3	Y	**3.3**	
51144	XM7015GB	332	69x40.5	61.5x15	24N28P	0.30	90	WYE	25	15.6Ω	93	2.9	8.0	20	30, 4xM4	15, 4xM3	Y	**5.0**	For yaw axis of RED EPIC&Frame(5kg)
51145	XM7015GB-SS	320	69x40.5	61.5x15	24N28P	0.30	90	WYE	25	15.6Ω	93	2.9	8.0	N/A	30, 4xM4	15, 4xM3	Y	**5.0**	